



**DIMENSIONS:**

WALK SURFACE WIDTHS (DIM A)	24"	36"	48"	60"	72"
CORRESPONDING OVERALL WIDTHS (DIM B)	42"	54"	66"	78"	90"

MODEL #	DIM C	DIM D	DIM E	DIM F	DIM G
3 STEP	36"	20"	65"	7"	7"
4 STEP	49"	21"	78"	10"	10"
5 STEP	62"	22"	91"	13"	13"
6 STEP	75"	24"	104"	17"	17"
7 STEP	88"	25"	117"	20"	20"

**SFR  
FLAT RAMP GANGWAY-G4**

**SPECIFICATIONS:**

- TOTAL LOAD CAPACITY - 500 lbs., HANDRAIL-200 lbs., MIDRAIL-100 lbs.
- AVAILABLE WORKING RANGE - 15° ABOVE TO 15° BELOW HORIZONTAL.
- 2.9" DIAMETER HANDRAIL WITH 1" DIAMETER GRAB BAR.
- BASE TREAD HOT DIPPED GALVANIZED PER ASTM A 123.
- GANGWAY BODY CONSTRUCTED OF ALUMINUM (STAINLESS STEEL-OPTIONAL).
- SELF SUPPORTING BY USE OF ADJUSTABLE CHAIN STOPS.
- SPRING COUNTERBALANCED FOR EASE OF OPERATION.
- LOAD BEARING PIVOT POINTS CONTAIN OIL IMPREGNATED BRONZE BEARINGS.
- AWS WELDING SPEC. D 1.1-D 1.2.
- ALL CRITICAL HARDWARE IS STAINLESS STEEL.

(23 DEC 2008)



**S F R  
FLAT RAMP GANGWAY**